

SAFETY DATA SHEET

C31-0057 CLEAR TEXTURE TC PURP

SECTION 1 – PRODUCT IDENTIFICATION

PRODUCT NAME: C31-0057 CLEAR TEXTURE TC PURP

PRODUCT NUMBER: 01C31-0057

SYNONYMS: PAINT

CAS NUMNER: Mixture

UN NUMBER: UN1263

EMERGENCY RESPONSE GUIDE NUMBER: GUIDE 128

RECOMMENDED USE: Paint

COMPANY INFORMATION: EMCO FINISHING PRODUCTS
470 CRESCENT STREET
JAMESTOWN, NEW YORK 14701
PHONE: (716) 483-1176
FAX: (716) 664-6680

EMERGENCY PHONE: (800) 424-9300 (CHEMTREC)

SECTION 2 – HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION: Flammable Liquid – 3
STOT SE – 3
STOT RE – 2
Skin Sensitization – 1
Reproductive Toxicity – 2
Carcinogenicity – 1A

SIGNAL WORD: WARNING



HAZARD PICTOGRAMS:

HAZARD STATEMENTS: **FLAMMABLE LIQUID AND VAPOR**
MAY CAUSE DROWSINESS OR DIZZINESS
MAY CAUSE AN ALLERGIC SKIN REACTION
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD
MAY CAUSE CANCER (ORAL)
MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE



SAFETY DATA SHEET

C31-0057 CLEAR TEXTURE TC PURP

PRECAUTIONARY STATEMENTS:

PREVENTION: Read label before use. Keep/store away from heat, hot surfaces, sparks, open flames and other ignition sources. Use only non-sparking tools. Avoid breathing vapors. Do not eat, drink or smoke when using this product. Use only in a well-ventilated area. Wear protective gloves and eye protection. In case of inadequate ventilation, wear respiratory protection.

RESPONSE: If swallowed, do NOT induce vomiting. Get medical attention. If on skin, rinse with plenty of water. If symptoms persist, get medical attention. If inhaled: remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms, get medical attention. If in eyes, rinse thoroughly for 15 minutes. Remove contact lenses and continue washing. Get medical attention. If on clothing, wash before reuse. In case of a fire, fight fire with normal precautions from a reasonable distance.

STORAGE: Store in a closed container. Keep in a cool well-ventilated place.

DISPOSAL: Dispose contents in accordance with federal, state, and local regulations.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE/MIXTURE:

INGREDIENT	PERCENT COMPOSITION	CAS NUMBER
Butyl Acetate	50-60%	123-86-4
Acrylic Polymers	25-35%	Non-Haz
Xylene	5-15%	1330-20-7
Epoxidized Soybean Oil	1-10%	8013-07-8
Ethanol	1-10%	64-17-5

SECTION 4 – FIRST-AID MEASURES

IF INHALED: Remove to fresh air. If not breathing or breathing is difficult, give oxygen or artificial respiration and get medical attention. Do not perform CPR.

IF SKIN CONTACT: Immediately wash skin with mild soap and large volumes of water. Remove contaminated clothing. Wash clothing before reuse. Get medical attention if symptoms persist.

IF EYE CONTACT: Thoroughly flush eyes with large volumes of clean, low pressure water for at least 15 minutes while holding eyelid open. Remove contact lenses, if worn, after initial flushing and then continue flushing. Get immediate medical attention.

IF SWALLOWED: Rinse mouth with water. Drink water. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention.



SAFETY DATA SHEET

C31-0057 CLEAR TEXTURE TC PURP

SECTION 5 – FIRE-FIGHTING MEASURES

- SUITABLE EXTINGUISHING MEDIA:** Water fog or spray, alcohol resistant foam, dry chemical, carbon dioxide.
- UNSUITABLE EXTINGUISHING MEDIA:** Do not use water in a tight stream.
- SPECIFIC FIREFIGHTING HAZARDS:** If possible, keep nearby containers cool. Heat may build enough internal pressure to rupture a closed container, potentially spreading the fire and increasing risk. Oxides of carbon and other possible toxic solids, vapors, and/or gases may be emitted.
- SPECIAL FIREFIGHTING EQUIPMENT/PROCEDURE:** Wear full protective clothing and self-contained breathing apparatus or air mask. Fight large fires from a safe distance. If possible do not allow discharge runoff into the water environment.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- PERSONAL PRECAUTIONS, PROTECTIVE EQUIPEMENT:** Handle in accordance with good industrial hygiene and safety practice. Use chemical resistant gloves and safety glasses with side shields or goggles. To prevent contact with skin, wear clothing covering all exposed areas.
- METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP/EMERGENCY PROCEDURE:** Ventilate the area. Avoid breathing dust or vapor. Use a self-containing breathing apparatus or air mask for larger spills. Remove all sources of sparks or ignition. Clean and dispose contaminated area into an appropriate disposal container.

SECTION 7 – HANDLING AND STORAGE

- HANDLING:** Handle in accordance with good industrial hygiene and safety practice. Do not smoke near chemicals.
- STORAGE:** Keep in cool, well-ventilated area away from any source of heat, sparks, or open flames. Keep container sealed tight when not in use. Ensure proper labeling on the container.

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

INGREDIENTS:

INGREDIENT	OSHA	ACGIH	CERCLA RQ	SARA 302 EHS	SARA 313	HUMAN CARCINOGEN



SAFETY DATA SHEET

C31-0057 CLEAR TEXTURE TC PURP

Butyl Acetate	PEL 150 ppm.	STEL 200 ppm.	5,000 lbs.	No	No	No
Acrylic Polymers	No data	No data	None Listed	No	No	No
Xylene	TWA 100 ppm.	STEL 150 ppm.	1,000 lbs.	No	Yes	No
Epoxidized Soybean Oil	No data	No data	None Listed	No	No	No
Ethanol	PEL 1,000 ppm.	TWA 1,000 ppm.	None Listed	No	No	No

RESPIRATORY PROTECTION:

Wear proper safety glasses and gloves. Avoid using contact lenses.

PROTECTIVE CLOTHING:

Wear clothes that protect from exposed skin. Clothing should be removed and washed after chemical usage.

VENTILATION:

Ensure that the area of usage is properly ventilated. If local exhaust ventilation system is not adequate, use a respiratory protection program.

ADDITIONAL MEASURES:

Wash hands before eating, drinking, smoking or using toilet facilities. Proper eyewash and safety shower facilities should be available.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
COLOR:	Colorless
ODOR:	Fruity Odor
ODOR THRESHOLD:	No data available
pH:	No data available
MELTING POINT/FREEZING POINT:	No data available
BOILING POINT/RANGE:	>130° F
FLASH POINT:	>0° F
EVAPORATION RATE:	No data available
LOWER EXPLOSIVE LIMIT:	~ 1%
UPPER EXPLOSIVE LIMIT:	~ 13%
VAPOR PRESSURE:	No data available
VAPOR DENSITY:	No data available
SPECIFIC GRAVITY:	0.923
SOLUBILITY IN WATER:	No data available
SOLUBILITY IN OTHER SOLVENTS:	No data available
PARTITION COEFFICIENT (N-OCTANOL/WATER):	No data available
AUTO-IGNITION TEMPERATURE:	No data available
DECOMPOSITION TEMPERATURE:	No data available
VISCOSITY:	No data available
VOC:	5.18 lbs./gallon

SECTION 10 – STABILITY AND REACTIVITY



SAFETY DATA SHEET

C31-0057 CLEAR TEXTURE TC PURP

CHEMICAL STABILITY:	Stable under normal conditions of use
HAZARDOUS POLYMERIZATIONS:	None anticipated under normal conditions of use
HAZARDOUS DECOMPOSITION PRODUCTS:	None anticipated under normal conditions of use
CONDITIONS TO AVOID:	Keep away from heat, sparks, open flame, static electricity, and all ignition sources.
INCOMPATIBLE MATERIALS:	Oxidizers

SECTION 11 – TOXICOLOGICAL INFORMATION

MEDICAL CONDITION AGGRAVATED:	Pre-existing medical conditions in the following systems or organs may be aggravated by exposure to this product: Skin (dermatitis), eyes, liver, kidneys, nervous system, respiratory system (asthma, lungs). Repeated or prolonged exposure could produce target organ damage.
INHALATION:	High concentrations may lead to Central Nervous System effects, including drowsiness, dizziness, nausea, headaches, paralysis, and possible unconsciousness. High vapor concentrations are irritating to the respiratory system and the eyes. Prolonged or repeated exposure may cause liver or kidney damage.
INGESTION:	Product may be harmful or fatal if swallowed, as well as produce potential lung damage. It may produce Central Nervous System effects including dizziness, loss of balance and coordination, coma, or even death. It also is an irritant to the mouth, throat, and stomach.
EYES:	The product will potentially cause moderate to significant eye irritation.
SKIN:	Contact with the solution may cause mild to moderate skin irritation. Repeated contact may result in defatting and drying/cracking of the skin, which could result in significant skin irritation and dermatitis (rash). Skin absorption may produce systemic toxicity.

SECTION 12 – ECOLOGICAL INFORMATION

PERSISTENCE AND DEGRADABILITY:	No data available
BIO ACCUMULATIVE POTENTIAL:	No data available
MOBILITY IN SOIL:	No data available
OTHER ADVERSE EFFECTS:	No data available



SAFETY DATA SHEET

C31-0057 CLEAR TEXTURE TC PURP

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state and local regulations.

SECTION 14 – TRANSPORT INFORMATION

UN NUMBER: UN1263
UN PROPER SHIPPING NAME: PAINT
TRANSPORT HAZARD CLASS: 3
PACKING GROUP: III
CONSTITUENTS: (Butyl Acetate)

SECTION 15 – REGULATORY INFORMATION

TSCA STATUS: All known components of this product are listed or are exempt from listing.

SARA SECTION 311/312:

ACUTE:	Yes
CHRONIC:	Yes
FIRE:	Yes
REACTIVE:	No
PRESSURE RELEASE:	No

HMIS HEALTH: 2
HMIS FLAMMABILITY: 3
HMIS REACTIVITY: 0
HMIS PERSONAL PROTECTION: X

SECTION 16 – OTHER INFORMATION

PRODUCT REVISION DATE: 9/23/2010
SDS REVISION DATE: January 17, 2018
SDS REVISION NUMBER: 1